



ARYAKEM 880

Long oil 70% Weight: 190kg

TYPE:

LONG OIL ALKYD RESIN BASED ON SOYA FATTY ACID

DELIVERY FORM:

ARYAKEM-880 -M70 70 ±1 % in Mineral spirit

INTRODUCTION:

Long Oil Alkyd Resins are commonly alkyd resin based on Soya bean fatty acid and Pentaerythritol. They are recommended for manufacturing architectural paint , wood, metal primers and are also used in printing industry.

<u>SPECIFICATIONS</u>	<u>ARYAKEM-880 -M70</u>
Oil type	Soya Fatty Acid
Alcohol type	Pentaerythritol
Oil Content	62%
Acid value (max)	10 (mg KOH/gr)
Viscosity @ 25 °c (stoke)	120-170
Color (Gardner)	4 (MAX)
Non-volatile content	70 ±1%
Solvent (s)	Mineral spirit

PROPERTIES:

- Good surface & deep drying.
- Good gloss & gloss retention
- Excellent coverage
- Accept the maximum level of filler
- Excellent pigment wetting & dispersion

APPLICATIONS:

- Gloss decorative architectural paints.
- Architectural and industrial varnishes
- Paint paste & building putty
- Spray

SOLUBILITY:

N- Butanol, Ketons, Xylene , White spirit , N-Butyl Acetate

COMPATIBILITY:

Compatibility with other medium resins.It must be checked before use.

STORAGE & STABILITY:

The shelf life of the products is 24 months if kept in a cool and dry place (5-30 °C) in original sealed drums. Keep away from any source of heat.

THE OFFERED RECOMMENDATIONS ARE BASED UPON OUR EXISTING KNOWLEDGE MERELY TO BE DEEMED AS START FORMULATIONS. THEREFORE, THERE IS NO GUARANTEE, I.E., WE ASSUME NO LIABILITY IN THIS REGARD AND THIS IS BECAUSE THE APPLICATION METHODS AND CONSUMPTION CONDITIONS ARE OUT OF OUR CONTROL. HENCE, THE ESTEEMED CONSUMERS ARE TO EVALUATE THE FORMULATIONS IN THEIR OWN LABS PRIOR TO PRODUCTION.

Website: www.goodrichkimya.com

Email: info@goodrichkimya.com

Adress: Fatih mah Atatürk Cd No:55/2 Gaziemir / İzmir

+90 552 608 0011

GSM: +90 530 707 5491

+90 232 608 1111

+90 232 608 2222