



ARYAKEM Ca-4

TYPE:

CALCIUM DRIER

DELIVERY FORM:

ARYAKEM-Ca-4

INTRODUCTION:

Calcium octate is used to react with possible precipitate. This dryer has properties such as spreading and wetting properties and reduces the absorption of the dryers by pigments.

SPECIFICATIONS:

<u>SPECIFICATIONS</u>	<u>CALCIUM DRIER</u>
Apearence	Yellow liquid
Metal Content	4 ± 0.2%
Density @ 25 °c	1 ± 0.01 (gr / cc)
Solvent (s)	Xylene
Viscosity @ 25 °c (stoke)	1-4
Acid Value	65

PROPERTIES:

- Reduced curing time & Prevent to settling
- Short gel time
- Good pigment wetting
- Good pigment spreading

APPLICATIONS:

- Aid drier for air drying systems

PRODUCT SOLUBILITY TITLE:

Aromaticts and Aliphatic solvents

PACKING:

190 kg net in new iron drum.

SOLUBILITY:

Methyl Ethyl Ketons, Xylene , N-Butyl Acetate, Mineral spirit , N- Butanol (limited)

COMPATIBILITY:

Compatibility with long and medium Alkyd resins and the other drier. it must be checked before use.

STORAGE & STABILITY:

The shelf life of the products is 12 months if kept in a cool and dry place (5-30 °C) in original sealed drums. Keep away from any source of heat.

THE OFFERED RECOMMENDATIONS ARE BASED UPON OUR EXISTING KNOWLEDGE MERELY TO BE DEEMED AS START FORMULATIONS. THEREFORE, THERE IS NO GUARANTEE, I.E., WE ASSUME NO LIABILITY IN THIS REGARD AND THIS IS BECAUSE THE APPLICATION METHODS AND CONSUMPTION CONDITIONS ARE OUT OF OUR CONTROL. HENCE, THE ESTEEMED CONSUMERS ARE TO EVALUATE THE FORMULATIONS IN THEIR OWN LABS PRIOR TO PRODUCTION.

Website: www.goodrichkimya.com**Email:** info@goodrichkimya.com**Adress:** Fatih mah Atatürk Cd No:55/2 Gaziemir / İzmir

+90 552 608 0011
GSM: +90 530 707 5491
+90 232 608 1111
+90 232 608 2222