



ARYAKEM Pb-24

TYPE:

LEAD DRIER

DELIVERY FORM:

ARYAKEM-Pb-24

INTRODUCTION:

Used as an octate lead and auxiliary dryer and with cobalt dryer for deep drying of paint . Due to its polymerization properties, it increases the stability, hardness and water resistance. In aluminum paints, this dryer is not recommended.

SPECIFICATIONS:

<u>SPECIFICATIONS</u>	<u>LEAD DRIER</u>
Apearance	Yellow liquid
Metal Content	24 ± 0.2%
Density @ 25 °c	1.27 ± 0.02(gr / cc)
Solvent (s)	Xylene
viscosity @ 25 °c (stock)	1-4

PROPERTIES:

- Reduced and speed up curing time.
- Good pigment wetting
- Excellent drying power
- Resistance to Settling

SOLUBILITY:

Methyl Ethyl Ketons, Xylene , N-Butyl Acetate, N- Butanol (limited) , Mineral spirit (limited)

PACKING:

250 kg net in new iron drum.

COMPATIBILITY:

Compatibility with long and medium Alkyd resins and the other driers such as Cobalt,Manganese and Calcium. it must be checked before use.

STORAGE & STABILITY:

The shelf life of the products is 12 months if kept in a cool and dry place (5-30 °C) in original sealed drums. Keep away from any source of heat..

THE OFFERED RECOMMENDATIONS ARE BASED UPON OUR EXISTING KNOWLEDGE MERELY TO BE DEEMED AS TART FORMULATIONS. THEREFORE, THERE IS NO GUARANTEE, I.E., WE ASSUME NO LIABILITY IN THIS REGARD AND THIS IS BECAUSE THE APPLICATION METHODS AND CONSUMPTION CONDITIONS ARE OUT OF OUR ONTROL. HENCE, THE ESTEEMED CONSUMERS ARE TO EVALUATE THE FORMULATIONS IN THEIR OWN LABS PRIOR TO RODUCTION.

Website: www.goodrichkimya.com

Email: info@goodrichkimya.com

Adress: Fatih mah Atatürk Cd No:55/2 Gaziemir / İzmir

+90 552 608 0011

GSM: +90 530 707 5491

+90 232 608 1111

+90 232 608 2222