



## ARYAKEM 409 - X60

### Performance Index of Liquid Resin:

Viscosity at 25°C (Gardner)	40 – 80 Sec
Solid Content	60 ± 1%
Acid Value	Max 8 mgKOH/g
Colour	Max 6 Gardner
Solvent	Xylene
Fatty acid	Soybean
Oil length	29 %

### Product Description:

- Perfect hardness
- Fast surface drying and deep drying
- High gloss and gloss retention
- Excellent adhesion and flexibility
- Excellent pigment wetting and dispersing
- Polishable

### Product Application:

- Industrial air-drying top coats
- Nitro cellulose paint for wood and metal
- Stoving paints and lacquers
- Anti-corrosion primers

### Storage Conditions and Shelf Life:

This product must be stored in its original sealed steel drum in a cold and dry place away from fire, heat source and direct sunlight in temperatures between 5-30°C. Under these conditions, the shelf life of this product will be maximum 12 months from delivery time.

### Packaging:

200 kg net in steel drum

### Remark:

Solid content, Viscosity and other qualitative parameters, are customizable based on customer requirements

**Website:** [www.goodrichkimya.com](http://www.goodrichkimya.com)

**Email:** [info@goodrichkimya.com](mailto:info@goodrichkimya.com)

**Address:** Fatih mah Atatürk Cd No:55/2 Gaziemir / İzmir

+90 552 608 0011

**GSM:** +90 530 707 5491

+90 232 608 1111

+90 232 608 2222