



ARYAKEM 410 - X65

Performance Index of Liquid Resin:

Viscosity at 25°C (Gardner)	120 – 180 Sec
Solid Content	65 ± 1%
Acid Value	Max 8 mgKOH/g
Colour	Max 6 Gardner
Solvent	Xylene
Fatty acid	Soybean
Oil length	29 %

Product Description:

- Perfect hardness
- Fast surface drying and deep drying
- High gloss and gloss retention
- Excellent adhesion and flexibility
- Excellent pigment wetting and dispersing
- Polishable

Product Application:

- Industrial air-drying top coats
- Nitro cellulose paint for wood and metal
- Stoving paints and lacquers
- Anti-corrosion primers

Storage Conditions and Shelf Life:

This product must be stored in its original sealed steel drum in a cold and dry place away from fire, heat source and direct sunlight in temperatures between 5-30°C. Under these conditions, the shelf life of this product will be maximum 12 months from delivery time.

Packaging:

200 kg net in steel drum

Remark:

Solid content, Viscosity and other qualitative parameters, are customizable based on customer requirements

Website: www.goodrichkimya.com

Email: info@goodrichkimya.com

Adress: Fatih mah Atatürk Cd No:55/2 Gaziemir / İzmir

+90 552 608 0011

GSM: +90 530 707 5491

+90 232 608 1111

+90 232 608 2222